

TECHNICAL SPECIFICATIONS

Model Azteca A Series	A-446	A-456		A-501		A-666		A-669		A-6612		A-6615		A-6618	
Doors(s)	Single	Single	Double	Single	Double	Single	Double	Single	Double	Single	Double	Single	Double	Single	Double
Inner chamber dimensions W x H x D (mm)	406 x 406 x 670	500 x 500 x 700	500 x 500 x 735	500 x 500 x 1000	500 x 500 x 1035	660 x 660 x 705	660 x 660 x 740	660 x 660 x 1000	660 x 660 x 1035	660 x 660 x 1265	660 x 660 x 1300	660 x 660 x 1555	660 x 660 x 1590	660 x 660 x 2000	660 x 660 x 2035
Chamber volume	110 L	175 L	183 L	250 L	258 L	307 L (4 STU)	322 L (4 STU)	435 l (6 STU)	450 l (6 STU)	551 L (8 STU)	566 L (8 STU)	677 L (10 STU)	692 L (10 STU)	841 L (12 STU)	886 L (12 STU)
External dimensions W x H x D (mm)	660 x 1900 x 910	970 x 1810 x 1005		970 x 1810 x 1305		1130 x 1960 x 1010		1130 x 1960 x 1305		1130 x 1960 x 1570		1130 x 1960 x 1860		1130 x 1960 x 2306	
Approximate weight	350 kg	600 kg		750 kg		850 kg		1000 kg		1150 kg		1250 kg		1800 kg	
Power supply *	3 ph. 380-400 V, 50/60 Hz														
Power without steam generator	2 kW														
Power of optional steam generator	12 kW	18 kW		27 kW		27 kW		36 kW		54 kW		63 kW		72 kW	
Available sterilization cycles	Flash 134 °C / Unwrapped 134 °C / Wrapped 134 °C / Prion 134 °C / Porous 121 °C														
Available test cycles	Bowie & Dick test / Vacuum test														
Touch-screen display	LCD 5.7" Color Graphic - (10" optional)														
Cover	Stainless steel														
Doors(s) type	Automatic vertical sliding door(s)														

* Adjustable to different voltage systems